

HDPE, PP & Plastic Manhole machining center CNC control Horizontal boring machine

Model: SYB 2000MM

Special design to meet requirement of customer to machine holes on plastic manholes of size 600mm to 2000mm. Hole size 100mm to 1000mm.




Model SYB 2000MM



Human machine interface



Control drives



360 degree rotating bed



Special clamp for manholes



Adjustable clamp 600 to 2000mm



Machining 100mm hole



Rotation after machining



Machining 800mm hole



800mm hole




Inserting inlet out let pipes




Plastic welding





Overall Dimensions






Specification		
HDPE & PP Manhole machining center Model: SYB 2000MM		
No	Item	Details
1.	CNC system	GSK GSK983M (three-axis 3 linkage), Four feed shafts plus and one servo-feed main shaft
		X-axis: 10N.M servo motor,
		Y-axis: 15N.M servo motor
		Z axis: 15N.M servo motor
		A-axis (Table rotation axis): 8N.M servo motor.
		Main shaft: 5.5KW servo motor, stepless speed regulation.
2.	Mechanical device	All Guides are used rolling guides and automatic lubrication system. With dust proof and ball lead screw drive/ transmission.
3	Automatic rotary working table	Hole cutting one time only without manually exchange the pipe direction.
		Table size 800 × 800mm
		Assistant working table size: ø2000mm
		Max. Clamping Dia. ø2000mm
4.	Axis	X-axis (Horizontal moving axis): Max travel distance 1500mm.
		Z axis (Facing Main shaft axis) Max travel distance of 2500mm.
		Y axis (Vertical moving axis) Max travel distance of 2500mm, with power protect device (Brake device).
5.	Main shaft	Rotating Speed: 20-1500 rpm/min
		Tool shank taper: BT40, with Pneumatic clamping / release
		Tool adjustable distance: ø50-ø650mm
6.	Guides	Provide Guides protection and automatic intermittent screw lubrication pumps for continuous lubrication.

山东鑫盟制造有限公司 SYB EAST CO. LTD

Financial Street C-609, No. 5097 Shengli East Street, Kuiwen, Weifang City, Shandong Province, China-261041. Tel: +86.136.9636.4788, Fax: +86.536.8286690, Email: sybeastco@yahoo.com



Turning Table for HDPE, PP & Plastic Manholes Welding Model: SYB 2000RT



Specification Item **Specifications** Material: Carbon steel 45mm A3 Table Dia.: 2100mm Variable-frequency motor, speed adjustable 0~5 rounds/ min Motor Power: 0.37KW **Frequency Converter** Mitsubishi Stand for table Material: Carbon steel Foot Operator switch Accelerator type NMRV040/090-500-YVPEJ0.37 Gear Box Made in China, Voltage 1¢, 230V,50Hz; 3¢, 380V,50Hz Max. Weight can bear 2 Tons



Financial Street C-609, No. 5097 Shengli East Street, Kuiwen, Weifang City, Shandong Province, China-261041. Tel: +86.136.9636.4788, Fax: +86.536.8286690, Email: sybeastco@yahoo.com